

Link do produktu: <https://www.skyrc.pl/skyrc-t6755-55w7a-acdc-oryginalna-ladowarka-p-152.html>

SkyRC T6755 55W/7A AC/DC Oryginalna ładowarka

| | |
|------------------|------------------------------|
| Cena | 319,00 zł |
| Dostępność | Aktualnie niedostępny |
| Czas wysyłki | 24 godziny |
| Numer katalogowy | 150 |
| Kod producenta | SK-100064 |
| Producent | SkyRC |

Opis produktu

Specyfikacja

| | |
|--------------------------|---|
| Input Voltage | AC Input: 100-240V/DC Input: 11-18V |
| Controls | Color LCD Touch Screen |
| Display Type | 65.85*49.63mm graphic touch sensitive LCD 3.2"(320*240 dot) screen and four color theme |
| Display Backlight | White |
| PC Communications | USB Port for PC Control & Firmware Upgrade |
| Case Material | Plastic |
| Cooling System | Built-in, one 40*40*10mm fan |
| Case Size | 140*165*60mm |

| | |
|----------------------------------|---|
| Weight | 540g |
| External Port | Balance Socket-XH, Temperature Probe Socket, DC Input, USB port for PC, AC Input Power Port |
| Delta Peak Detection | NiCd: 3-15mV/cell NiMH: 3-15mV/cell |
| Charge Cutoff Temperature | 20-80°C (adjustable) |
| Charge Voltage | NiCd/NiMH: Delta peak detection LiPo: 4.18-4.3V/cell Lilon: 4.08-4.2V/cell |
| Balance Current | 200mA/cell |
| Reading Voltage Range | 0.3-5.0V/cell |
| Battery Types/Cells | NiCd/NiMH: 1-15cells LiPo/Lilon/LiFe: 1-6cells Pb: 2-20V |
| Battery Capacity Range | NiCd/NiMH: 100-20,000mAh LiPo/Lilon/LiFe: 100-20,000mAh Pb: 100-20,000mAh |
| Charge Current | 0.1-7.0A |
| Safety Timer | 1-720 minutes, Off |

| | |
|----------------------------------|---|
| Charge Wattage | 55W |
| Discharge Current | 0.1-2.0A ($\pm 10\%$) |
| Discharge Cut-off Voltage | NiCd/NiMH: 0.1-1.1V/cell LiPo: 3.0-3.3V/cell Lilon: 2.9-3.2V/cell |
| Discharge Wattage | 5W |
| Balance Cells | 6 cells |
| Memory | 5 different charge/discharge profiles |
| Charge Method | CC/CV for lithium types and lead (pb) batteries, Delta-peak Sensitivity for NiMH/NiCd |

